

## § 122.606

in paragraph (b) by removing the words “vessel marked” and adding, in their place, the words “vessel or company marked”, effective Oct. 30, 1997.

### § 122.606 Escape hatches and emergency exits.

All escape hatches and other emergency exits used as means of escape must be marked on both sides in clearly legible letters at least 50 millimeters (2 inches) high: “EMERGENCY EXIT, KEEP CLEAR”, unless such markings are deemed unnecessary by the cognizant OCMI.

### § 122.608 Fuel shutoff valves.

Remote fuel shutoff stations must be marked in clearly legible letters at least 25 millimeters (1 inch) high indicating purpose of the valve and direction of operations.

### § 122.610 Watertight doors and watertight hatches.

Watertight doors and watertight hatches must be marked on both sides in clearly legible letters at least 25 millimeters (1 inch) high: “WATERTIGHT DOOR—KEEP CLOSED” or “WATERTIGHT HATCH—KEEP CLOSED”, unless such markings are deemed unnecessary by the cognizant OCMI.

[CGD 85-080, 61 FR 935, Jan. 10, 1996, as amended by CGD 97-057, 62 FR 51047, Sept. 30, 1997]

### § 122.612 Fire protection equipment.

(a) Complete but simple instructions for the operation of a fixed gas fire extinguishing system must be located in a conspicuous place at or near each pull box and stop valve control and in the space where the extinguishing agent cylinders are stored. If the storage cylinders are separate from the protected space, the instructions must also include a schematic diagram of the system and instructions detailing alternate methods of releasing the extinguishing agent should the local manual release or stop valve controls fail to operate. Each control valve to a distribution line must be marked to indicate the space served.

(b) An alarm for a fixed gas fire extinguishing system must be clearly and conspicuously marked “WHEN ALARM

## 46 CFR Ch. I (10-1-97 Edition)

SOUNDS—VACATE AT ONCE. CARBON DIOXIDE BEING RELEASED.” Where a different extinguishing agent is installed, that agent shall be marked in place of “carbon dioxide.”

(c) Each distribution line valve of a fixed gas fire extinguishing system and the fire main, must be plainly, conspicuously, and permanently marked indicating the space served.

(d) A manual fire alarm box must be conspicuously marked in clearly legible letters “IN CASE OF FIRE BREAK GLASS”.

(e) An alarm for an automatic fire detecting system or a manual alarm system must be conspicuously marked in clearly legible letters “FIRE ALARM”.

(f) An alarm for an automatic sprinkler system must be conspicuously marked in clearly legible letters “SPRINKLER ALARM”.

(g) An alarm bell for a smoke detecting system must be conspicuously marked in clearly legible letters “SMOKE DETECTION ALARM”.

(h) A control cabinet or space containing valves, manifolds, or controls for any fixed gas fire extinguishing system must be conspicuously marked in clearly legible letters “CARBON DIOXIDE FIRE EXTINGUISHING APPARATUS”, or as otherwise required by the cognizant OCMI. Where a different extinguishing agent is installed, that agent shall be marked in place of “carbon dioxide.”

[CGD 85-080, 61 FR 935, Jan. 10, 1996, as amended at 62 FR 51353, Sept. 30, 1997]

EFFECTIVE DATE NOTE: By CGD 85-080, 62 FR 51353, Sept. 30, 1997, § 122.612 was amended in paragraph (b) by removing the words “in clearly legible letters” and by removing the word “ALARMS” and adding, in its place, the word “ALARM” and, in paragraph (f), by removing the word “cleared” and adding, in its place, the word “clearly”, effective Oct. 30, 1997.

### § 122.614 Portable watertight containers for distress flares and smoke signals.

Portable watertight containers for distress flares and smoke signals shall be of a bright color, and containers shall be clearly marked in legible contrasting letters at least 12.7 millimeters (0.5 inches) high: “DISTRESS SIGNALS”.